

IMPORTANT: OPW products should be used in compliance with applicable federal, state, provincial, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and materials to be handled. OPW MAKES NO WARRANTY OF FITNESS FOR A PARTICULAR USE. All illustrations and specifications in this literature are based on the latest product information available at the time of publication. OPW reserves the right to make changes at any time in prices, materials, specifications and models and to discontinue models without notice or obligation.



OAS400B 3/4" Nozzle Reconnectable Breakaway (OAS400B)



The B/N OPW OAS400 3/4" Breakaway with Anchor Strap is designed for in-line use with any LPG fueling system. Valve inlet has 3/4" npt threads. All B/N OPW valves are built to exacting engineering specifications for fueling safety and efficiency.

Table of Contents:

1. Features
2. Ordering Specifications

Key Features Include:

- Durable Construction – Heavy-duty brass, aluminum and steel construction provides excellent corrosion resistance in the harsh fueling environment.
- Added Safety – Anchor strap allows for installation anywhere, and added assurance.
- Patented Front Compression Collar Provides Ease of Use – Breakaway can be reconnected without tools by simply turning the front ring to compress the locking sleeve. Reinsert the breakaway half of the safety valve and then unscrew front ring to allow locking sleeve to return to its original position.
- Individually Leak Tested and Inspected.

Materials

Body: Brass

Internal Components: Brass

Seals: Specially formulated polymers and elastomers specific to LPG applications.

Specifications:

Maximum Operating Pressure: 350 psi

Separation Force: 150-200 lbs.

Weight: 1.05 kg

Temperature Range: -40° C to 85° C

(-40° F to 185° F)

Ordering Information

Product No.	Thread Size	Material	Maximum Allowable Service Pressure
OAS400B	3/4" NPT Female	Brass	350 psi

